

# Quantum Algorithms for Matching Problems

Sebastian Dörn

Institut für Theoretische Informatik, Universität Ulm, 89069 Ulm, Germany  
sebastian.doern@uni-ulm.de

**Abstract.** We present quantum algorithms for the following matching problems in unweighted and weighted graphs with  $n$  vertices and  $m$  edges:

- Finding a maximal matching in general graphs in time  $O(\sqrt{nm} \log^2 n)$ .
- Finding a maximum matching in general graphs in time  $O(n\sqrt{m} \log^2 n)$ .
- Finding a maximum weight matching in bipartite graphs in time  $O(n\sqrt{m}N \log^2 n)$ , where  $N$  is the largest edge weight.
- Finding a minimum weight perfect matching in bipartite graphs in time  $O(n\sqrt{nm} \log^3 n)$ .

These results improve the best classical complexity bounds for the corresponding problems. In particular, the second result solves an open question stated in a paper by Ambainis and Špalek [AS06].

## 1 Introduction

A matching in a graph is a set of edges such that for every vertex at most one edge of the matching is incident on the vertex. The task is to find a matching of maximum cardinality. The matching problem has many important applications in graph theory and computer science.

In this paper we study the complexity of algorithms for the matching problems on quantum computers and compare these to the best known classical algorithms. We will consider different versions of the matching problems, depending on whether the graph is bipartite or not and whether the graph is unweighted or weighted.

For unweighted graphs, the best classical algorithm for finding a matching of maximum cardinality is based on augmenting paths and has running time  $O(\sqrt{nm})$  (see Micali and Vazirani [MV80]). Mucha and Sankowski [MS04] present an algorithm based on matrix multiplication that finds a maximum matching in general graphs in time  $O(n^\omega)$ , where  $2 \leq \omega \leq 2.38$  is the exponent of the best matrix multiplication algorithm.

Ambainis and Špalek [AS06] published an  $O(n^2(\sqrt{m/n} + \log n) \log^2 n)$  quantum time algorithm for computing a maximum matching. But this quantum algorithm is in no case better than the best classical algorithm from [MV80] and [MS04]. The authors of [AS06] state as an open question, to improve with a quantum algorithm the fastest known classical algorithm by Micali and Vazirani [MV80]. We solve this question by presenting an  $O(n\sqrt{m} \log^2 n)$  quantum

time algorithm for finding a maximum matching in general graphs. This algorithm is faster than the best classical algorithms for graphs with  $m > n \log^4 n$ .

For bipartite graphs the best classical matching algorithm has running time  $O(\sqrt{nm})$  (see Hopcroft and Karp [HK73]). Ambainis and Špalek [AS06] improved this bound with an  $O(n\sqrt{m} \log^2 n)$  quantum algorithm for computing a maximum matching in these graphs. The algorithm is polynomially faster than the best classical algorithm, but not necessarily optimal. The time complexity of our quantum algorithm for the maximum matching problem in general graphs matches the complexity given in the algorithm from [AS06] for the restricted case of bipartite graphs.

If we consider weighted graphs, the best classical algorithms for computing a maximum weight matching in bipartite graphs were developed by Gabow and Tarjan [GT89] with running time  $O(\sqrt{nm} \log(nN))$  and Kao, et al. [KLST01] with time complexity  $O(\sqrt{nW}/k(n, W/N))$ , where  $k(x, y) = \log x / \log(x^2/y)$ ,  $N$  is the largest edge weight and  $W$  is the total edge weight of  $G$ .

We construct a quantum algorithm using the decomposition theorem of [KLST01], and get a running time of  $O(n\sqrt{m}N \log^2 n)$  for computing a maximum weight matching in bipartite graphs. If the largest edge weight  $N$  is constant, then we get an  $O(n\sqrt{m} \log^2 n)$  time algorithm. This is faster than the best classical algorithms for this problem.

Berzina et al. [BDFLS04] and Zhang [Zha04] showed, that  $\Omega(n^{3/2})$  quantum queries to the adjacency matrix are required for computing a maximum matching in a bipartite graph. This implies a quantum lower bound of  $\Omega(n^{3/2})$  for the quantum time complexity. Since the bipartite maximum matching problem is a special case of the other maximum matching problems, it follows that the  $\Omega(n^{3/2})$  lower bound holds for all the maximum matching problems considered here. We show that the same lower bound holds also for the maximal matching problem. Then we obtain a matching upper bound for this problem, thus showing that the quantum query complexity of the problem is  $\Theta(n^{3/2})$ . For the running time we prove an upper bound of  $O(\sqrt{nm} \log^2 n)$ .

Our results are proved using several techniques: Grover search [Gro96], quantum depth first search, topological numbering and quantum running time analysis of classical algorithms. For the case of weighted matching algorithms we use the quantum graph algorithms of Dürr [DHHM04] and as well as our new maximum matching algorithm.

The paper is organized as follows: In section 2 we give necessary definitions and facts about graph theory and quantum computing. In section 3 we present quantum algorithms for unweighted matching problems. We give a quantum algorithm for computing a maximal matching in general graphs in time  $O(\sqrt{nm} \log^2 n)$ . Then we present a maximum matching quantum algorithm for general graphs in time  $O(n\sqrt{m} \log^2 n)$ . In section 4 we give quantum algorithms for the weighted matching problems. We show, that finding a maximum weight matching in bipartite graphs can be done in time  $O(n\sqrt{m}N \log^2 n)$  and finding a minimum weight perfect matching in bipartite graphs can be done in time  $O(n\sqrt{nm} \log^3 n)$ . We end with a section with conclusion and open problems.

## 2 Preliminaries

### 2.1 Graph Theory

Let  $G = (V, E)$  be an undirected graph, with  $V = V(G)$  and  $E = E(G)$  we denote the set of vertices and edges of  $G$ . Let  $n = |V|$  be the number of vertices and  $m = |E|$  the number of edges of  $G$ . We denote by  $N_G(v)$  the set of all vertices adjacent to  $v \in V$  and  $d_G(v) := |N_G(v)|$ . The graph  $G_{-S}$  is obtained from  $G$  by deleting the vertices  $S \subset V$  and the incident edges. We denote by  $[n]$  the set  $\{1, \dots, n\}$ .

**Definition 1** Let  $G = (V, E)$  be an undirected graph, a *matching* is a subset  $M \subseteq E$  such that for all vertices  $v \in V$ , at most one edge of  $M$  is incident on  $v$ . We say that a vertex  $v \in V$  is *matched* by  $M$  if some edge in  $M$  is incident on  $v$ , otherwise  $v$  is called *unmatched* or *free*. A matching is called *perfect*, if all vertices of  $G$  are matched. The set  $M$  is called *maximal*, if there is no matching  $M' \subseteq E$  with  $M \subset M'$ . A *maximum matching* is a matching of maximum cardinality.

A *path* between two vertices  $s$  and  $t$  in  $G$  is a sequence  $(v_1, \dots, v_k)$  where  $k \geq 1$  and  $v_1, \dots, v_k$  are distinct vertices of  $G$  such that  $s = v_1$ ,  $t = v_k$  and  $\{v_i, v_{i+1}\} \in E$  for  $i = 1, \dots, k-1$ . For a matching  $M$ , a path  $P$  in  $G$  is called *alternating* in  $M$  if edges in  $P$  are alternately in  $M$  and not in  $M$ . An alternating path  $P$  is called *augmenting path* for the matching  $M$  if the two end vertices of  $P$  are unmatched by  $M$ .

We consider the following models for accessing information in undirected graphs:

**Adjacency matrix model:** Given is the adjacency matrix  $A \in \{0, 1\}^{n \times n}$  of  $G$  with  $A_{i,j} = 1$  iff  $\{i, j\} \in E$ . Weighted graphs are encoded by a weight matrix  $A$ , where  $A_{i,j}$  is the weight of edge  $\{i, j\}$ , and for convenience we set  $A_{i,j} = \infty$  if  $\{i, j\} \notin E$ .

**Adjacency list model:** Given are the degrees  $d_G(1), \dots, d_G(n)$  of the vertices and for every  $i \in V$  an array with its neighbours  $f_i : [d_G(i)] \rightarrow [n]$ . The value  $f_i(j)$  is the  $j$ -th neighbour of  $i$ . Weighted graphs are encoded by a sequence of functions  $f_i : [d_G(i)] \rightarrow [n] \times \mathbb{N}$ , such that if  $f_i(j) = (i', w)$  then there is an edge  $\{i, i'\}$  with weight  $w$  and  $i'$  is the  $j$ -th neighbour of  $i$ .

In the following, we denote by  $\mathbf{M}$  and  $\mathbf{L}$  the input model of the graph as adjacency matrix ( $\mathbf{M}$ ) and as adjacency list ( $\mathbf{L}$ ).

### 2.2 Quantum Computing

For the basic notation on quantum computing, we refer the reader to the textbook by Nielsen and Chuang [NC03].

**Quantum Complexity.** For the quantum algorithms included in this paper we use the following two complexity measures:

- The *quantum query complexity* of a graph algorithm  $\mathcal{A}$  is the number of queries to the adjacency matrix or to the adjacency list of the input graph made by  $\mathcal{A}$ .
- The *quantum time complexity* of a graph algorithm  $\mathcal{A}$  is the number of basic quantum operations made by  $\mathcal{A}$ .

*Remark 1.*

1. The quantum time complexity is always at least as large as the quantum query complexity, since each query takes one unit step.
2. For the most polynomial time quantum algorithms, the time complexity is equal the query complexity with a log factor.
3. In many graph problems where the graph has a large number of edges ( $m = \Theta(n^2)$ ), the number of queries to the adjacency matrix is the same as the number of queries to the adjacency list. An exception for example is the test whether a graph is connected (see [DHHM04]).

**Quantum Query Lower Bounds.** In this paper, we use the following special case of a method by Ambainis [Amb02] to prove lower bounds for the quantum query complexity.

**Theorem 1.** [Amb02] *Let  $A \subset \{0, 1\}^n, B \subset \{0, 1\}^n$  and  $f : \{0, 1\}^n \rightarrow \{0, 1\}$  such that  $f(x) = 1$  for all  $x \in A$ , and  $f(y) = 0$  for all  $y \in B$ . Let  $m$  and  $m'$  be numbers such that*

1. *for every  $(x_1, \dots, x_n) \in A$  there are at least  $m$  values  $i \in \{1, \dots, n\}$  such that  $(x_1, \dots, x_{i-1}, 1 - x_i, x_{i+1}, \dots, x_n) \in B$ ,*
2. *for every  $(x_1, \dots, x_n) \in B$  there are at least  $m'$  values  $i \in \{1, \dots, n\}$  such that  $(x_1, \dots, x_{i-1}, 1 - x_i, x_{i+1}, \dots, x_n) \in A$ .*

*Then every bounded-error quantum algorithm that computes  $f$  has quantum query complexity  $\Omega(\sqrt{m \cdot m'})$ .*

*Remark 2.*

1. A lower bound for the quantum query complexity implies also the same lower bound for the quantum time complexity.
2. The trivial upper bound for the quantum query complexity in graph theory is  $O(n^2)$ .

**Quantum Search.** A search problem is a subset  $P \subseteq [N]$  of the search space  $[N]$ . With  $P$  we associate its characteristic function  $f_P : [N] \rightarrow \{0, 1\}$  with

$$f_P(x) = \begin{cases} 1, & \text{if } x \in P, \\ 0, & \text{otherwise.} \end{cases}$$

Any  $x \in P$  is called a solution to the search problem. Let  $k = |P|$  be the number of solutions of  $P$ .

**Theorem 2.** [Gro96,BBHT98] *For  $k > 0$ , the expected quantum query complexity for finding one solution of  $P$  is  $O(\sqrt{N}/k)$ , and for finding all solutions, it is  $O(\sqrt{kN})$ . Furthermore, whether  $k > 0$  can be decided in  $O(\sqrt{N})$  quantum queries to  $f_P$ .*

We denote by  $\text{QUANTUM SEARCH}[f_P]$  an application of Grover's search algorithm which computes a solution  $x^*$ , i.e an element  $x^*$  of the search space of  $P$  with  $f_P(x^*) = 1$ .

*Remark 3.* Our quantum algorithms output an incorrect answer with a constant probability  $p$ . If we want to reduce the error probability to less than  $\epsilon$ , we repeat each quantum subroutine  $l$  times, where  $p^l \leq \epsilon$ . It follows, that we have to repeat each quantum subroutine  $l = O(\log n)$  times, to make the probability of a correct answer greater than  $1 - 1/n$ . This increases the running time of all our algorithms by a logarithmic factor. Furthermore, the running time of Grover search is bigger than its query complexity by another logarithmic factor.

### 3 Unweighted Matchings

We regard the following matching problems in unweighted graphs:

**Maximal Matching:** Given a graph  $G$ , compute a maximal matching in  $G$ .

**Maximum Matching:** Given a graph  $G$ , compute a maximum matching in  $G$ .

#### 3.1 Maximal Matching

In this section we construct a quantum query algorithm for the maximal matching problem. Then we prove that this algorithm is optimal in the adjacency matrix model.

Let  $H$  be a graph and  $v$  a vertex of  $H$ . For application of quantum search, we construct a search function  $f_{H,v} : V(H) \rightarrow \{0, 1\}$  with

$$f_{H,v}(u) = \begin{cases} 1, & \text{if } \{v, u\} \in E(H) \\ 0, & \text{otherwise.} \end{cases}$$

---

#### Algorithm 1 MAXIMAL MATCHING

---

**Input:** Graph  $G = (V, E)$  with  $V = \{v_1, \dots, v_n\}$ .

**Output:** Maximal matching  $M$ .

**Complexity:** **M:**  $O(n^{1.5})$ , **L:**  $O(\sqrt{nm})$  quantum queries.

```

1:  $M := \emptyset, H := G, k := 1$ 
2: while  $E(H) \neq \emptyset$  do
3:    $v = \text{QUANTUM SEARCH}[f_{H,v_k}]$ 
4:    $M := M \cup \{\{v_k, v\}\}$ 
5:    $H := H_{-\{v_k, v\}}$ 
6:    $k := k + 1$ 
7: end while

```

---

**Theorem 3.** *The quantum query complexity of the MAXIMAL MATCHING algorithm is  $O(n^{1.5})$  in the adjacency matrix model and  $O(\sqrt{nm})$  in the adjacency list model.*

*Proof.* In every step of the algorithm, we search with the Grover algorithm an adjacent edge of a vertex  $v_k$  in  $H$ . This can be done in  $O(\sqrt{n})$  quantum queries to the adjacency matrix. If there is no such an edge, we delete the vertex  $v_k$  from  $H$ . Otherwise we use the edge  $\{v_k, v\}$  for the matching  $M$ , and we delete the two vertices  $v_k$  and  $v$  from  $H$ .

In total we use  $O(n^{1.5})$  quantum queries to the adjacency matrix for computing a maximal matching. In the list model  $\sqrt{d_G(v_k)}$  queries are required for every vertex  $v_k$ , and in total we use  $\sum_{k=1}^n \sqrt{d_G(v_k)} = O(\sqrt{nm})$  quantum queries to the adjacency list. ■

**Corollary 1.** *The quantum time complexity of the MAXIMAL MATCHING algorithm is  $O(n^{1.5} \log^2 n)$  in the adjacency model and  $O(\sqrt{nm} \log^2 n)$  in the adjacency list model.*

Now we show that the MAXIMAL MATCHING quantum algorithm is optimal in the adjacency matrix model, by proving a quantum query lower bounds with the method of Ambainis [Amb02] and analog to [BDFLS04].

**Theorem 4.** *The maximal matching problem requires  $\Omega(n^{1.5})$  quantum queries to the adjacency matrix.*

*Proof.* We construct the sets  $A$  and  $B$  for the usage of Theorem 1. Let  $f$  be the Boolean function which is one, iff there is a maximal matching set of size  $n$ . The set  $A$  consists of all graphs  $G = (V, E)$  with  $|V| = 3n + 1$  satisfying the following requirements: 1. There are  $n$  mutually not connected red vertices. 2. There are  $2n$  green vertices not connected with the red ones. Green vertices are grouped in pairs and each pair is connected by edge. 3. There is a black vertex which is connected to all red and green vertices. Let  $M$  be the set of all edges between two green vertices of  $G$ . Then  $M$  is a maximal matching in  $G$  of size  $n$ . The value of the function  $f$  for all graphs  $G \in A$  is 1.

The set  $B$  consists of all graphs  $G' = (V, E)$  with  $|V| = 3n + 1$  satisfying the following requirements: 1. There are  $n - 2$  mutually not connected red vertices. 2. There are  $2n + 2$  green vertices not connected with red ones, green vertices are grouped in pairs and each pair is connected by edge. 3. There is a black vertex which is connected to all red and green vertices. The value of the function  $f$  for all graphs  $G' \in B$  is 0, since there no maximal matching of size  $n$  in  $G'$ .

From each graph  $G \in A$ , we can obtain  $G' \in B$  by adding one edge between two red vertices, then  $l = O(n^2)$ . From each graph  $G' \in B$ , we can obtain  $G \in A$  by deleting an edge between two green vertices, then  $l' = O(n)$ . By Theorem 1, the quantum query complexity is  $\Omega(\sqrt{l \cdot l'}) = \Omega(n^{1.5})$ . ■

### 3.2 Maximum Matching

The best classical algorithm for finding a matching of maximum cardinality in general graphs is based on augmenting paths and has running time  $O(\sqrt{nm})$ , see Micali and Vazirani [MV80]. Mucha and Sankowski [MS04] present an algorithm based on matrix multiplication that finds a maximal matching in general graphs in time  $O(n^\omega)$ , where  $2 \leq \omega \leq 2.38$  is the exponent of the best matrix multiplication algorithm.

Ambainis and Špalek [AS06] construct a  $O(n^2(\sqrt{m/n} + \log n) \log^2 n)$  quantum algorithm for computing a maximum matching. But this quantum algorithm is in no case better than the best classical algorithm from [MV80] and [MS04].

In this subsection we present an  $O(n\sqrt{m} \log^2 n)$  quantum time algorithm for finding a maximum matching in a general graphs. This algorithm is faster than the best classical one for computing a maximum matching in a graph with  $m > n \log^4 n$ .

We speed up the  $O(\sqrt{nm})$  algorithm by Micali and Vazirani [MV80]. This algorithm works in phases. In each phase a maximal set of disjoint minimum length augmenting paths is found, and the existing matching is increased along this paths. We implement such a phase in time  $O(\sqrt{mn} \log^2 n)$  with quantum search. Only  $O(\sqrt{n})$  such phases are needed for finding a maximum matching, see [HK73], [MV80].

First we determine the quantum query complexity of two basic graph problems, depth first search and topological numbering. We use this procedures in the quantum maximum matching algorithm.

**Depth First Search (DFS):** Given a graph  $G = (V, E)$  and a vertex  $s \in V$ . Compute a depth-first tree  $T$  from  $s$ . The tree  $T$  is rooted at  $s$  and contains all the vertices of  $G$  that are reachable from  $s$ .

**Lemma 1.** *The quantum query complexity of DFS is  $O(n^{1.5})$  in the adjacency matrix model and  $O(\sqrt{nm})$  in the adjacency list model.*

*Proof.* In DFS, we construct a tree  $T$  that contains all the vertices of  $G$  that are reachable from the root  $s$ . We can construct this tree by the following simple procedure: For each edge  $(s, w) \in E$  in which  $w$  has not been discovered by  $T$ , make  $w$  the next child of  $s$  in  $T$ , and recall the procedure with  $s = w$ .

We use Grover search to construct the tree  $T$ . Every vertex is discovered by  $T$  at most once. In the adjacency matrix model, every vertex is found in  $O(\sqrt{n})$  quantum queries, and in total we uses  $O(n^{1.5})$  quantum queries in the adjacency matrix model. In the list model, finding an adjacent vertex of  $s$  which has not been discovered uses  $O(\sqrt{d_G(s)})$  quantum queries. In total it holds  $\sum_s \sqrt{d_G(s)} = O(\sqrt{mn})$  quantum queries in the adjacency list model. ■

**Topological Numbering (TN):** Given a directed acyclic graph  $G = (V, E)$ . Compute a numbering  $I : V \rightarrow \{1, \dots, n\}$  for each vertex in  $G$ , such that each edge is directed from lower number to higher number, i.e. if  $(u, v) \in E$  then  $I(u) < I(v)$ .

**Lemma 2.** *The quantum query complexity of topological numbering is  $O(n^{1.5})$  in the adjacency matrix model and  $O(\sqrt{nm})$  in the adjacency list model.*

*Proof.* We grow a DFS path  $P$  until a sink  $t$  (vertex with outdegree 0) is reached. Then we set  $I(t) = n$ , decrease  $n$  by 1 and delete  $t$  from the path  $P$  and the graph  $G$ . We continue with the DFS procedure until  $G$  has no vertices.

In each iteration we grow the DFS path  $P$  by starting with the previous  $P$  and extending it, if possible. Since we use DFS, we apply Lemma 1 to obtain the quantum query complexity of topological numbering. ■

Before we explain the maximum matching algorithm, we give some important definitions.

**Definition 2** Let  $G = (V, E)$  be a graph and  $M$  be a matching in  $G$ .

- The *evenlevel* (*oddlevel*) of a vertex  $v$  is the length of a minimum even (odd) length alternating path from  $v$  to a free vertex, if there is one, and infinite otherwise.
- The *level* is the length of a minimum alternating path from  $v$  to a free vertex.
- A vertex is *outer* (*inner*) iff its level is even (odd). If  $v$  is outer (inner) then its oddlevel (evenlevel) will be referred to as the *other level* of  $v$ .
- An edge  $(u, v)$  in a graph  $G$  with matching  $M$  is called a *bridge* if either both  $\text{evenlevel}(u)$  and  $\text{evenlevel}(v)$  are finite, or both  $\text{oddlevel}(u)$  and  $\text{oddlevel}(v)$  are finite.
- A *blossom*  $B$  in a matched graph  $G$  is a cycle of odd length  $k$ , in which the edges are maximally matched. In every blossom there is one free vertex, called *basis* of  $B$ . The two vertices at distance  $\lfloor k/2 \rfloor$  from the basis are called *peaks* of  $B$ .
- Let  $u$  be a vertex of  $G$  which is not matched. If  $u$  is inner and  $\text{oddlevel}(u) = 2i + 1$  then  $v$  is called a *predecessor* of  $u$  iff  $\text{evenlevel}(v) = 2i$  and  $(u, v) \in E$ . If  $u$  is outer then  $v$  is a predecessor of  $u$  iff  $(u, v)$  is a matched edge.
- The *ancestor* is the transitive closure of the relation predecessor.

The classical algorithm by [MV80] for computing a maximal matching in a general graph consists of a main routine SEARCH, and three subroutines: BLOSS-AUG, FINDPATH and TOPOLOGICAL ERASE. We describe shortly the four parts of the algorithm, for details see [MV80]:

**SEARCH:**

Given a graph  $G = (V, E)$  and a matching  $M$ , SEARCH constructs simultaneously for every free vertex  $v$  of  $G$  a Breadth First Search (BFS) tree which is rooted at  $v$ , to find the odd and evenlevel of each vertex in  $G$ . At the start of the subroutine the two levels of each vertex of  $G$  are set to infinity. Then SEARCH grows the BFS trees by incrementing the search level by one each time.

When SEARCH detects that a certain edge  $(u, v)$  is a bridge, it calls the subroutine BLOSS-AUG with the parameter  $u$  and  $v$ .



**BLOSS-AUG:**

This subroutine is called with vertices  $u$  and  $v$  such that the edge  $(u, v)$  is a bridge. The result is either the formation of a new blossom, or a minimum augmenting path. A new blossom is formed if and only if the following condition holds:

1. There exist a vertex  $z$  such that  $z$  is an ancestor of vertex  $u$  and  $v$ .
2. The vertices  $u$  and  $v$  do not have any ancestors, other than  $z$ , whose level is equal to the level of  $z$ .

If the condition holds for bridge  $(u, v)$  and  $b$  is the vertex whose level is maximum, then the new blossom is the set of vertices  $w$  such that:

1. Vertex  $w$  does not belong to any other blossom when  $B$  is formed.
2. Either  $w = u$  or  $w = v$  or  $w$  is an ancestor of  $u$  or  $w$  is an ancestor of  $v$ .
3. The vertex  $b$  is an ancestor of  $w$ .

From this follows, that  $b$  is the base of  $B$  and  $u$  and  $v$  are the peaks of  $B$ .

BLOSS-AUG performs a Double Depth First Search (DDFS), consisting in growing two DFS trees  $T_l$  and  $T_r$  simultaneously, i.e. if at a certain stage, the centers of activities of  $T_l$  and  $T_r$  are at  $v_l$  and  $v_r$ , then the DDFS grows  $T_l$  if  $\text{level}(v_l) \geq \text{level}(v_r)$ , and it grows  $T_r$  otherwise.  $T_l$  and  $T_r$  are rooted at  $u$  and  $v$ .

For the special details of the DDFS see [MV80, page 21]. During the DDFS, the two trees can find two different free vertices, then an augmentation of the matching is possible.

**FINDPATH:**

When BLOSS-AUG finds the presence of a minimum augmenting path, we use FINDPATH to search one such a path  $P$ . FINDPATH is called with two vertices  $v_h$  and  $v_l$  and a blossom  $B$  as parameters. It holds  $\text{level}(v_h) \geq \text{level}(v_l)$  and they both belong to a common minimum augmenting path.

The procedure returns a path between  $v_l$  and  $v_r$  with a DFS starting at  $v_h$  to find  $v_l$ . The present matching is increased along the minimum augmenting path  $P$ .

**TOPOLOGICAL ERASE:**

After FINDPATH has found the minimum augmenting path  $P$  and the matching has been increased along this path, this subroutine deletes from the graph the path  $P$  and all those edges which cannot be part of a minimum augmenting path disjoint from  $P$ .

This subroutine uses a topological sort. Each vertex has a counter which at any stage indicates the number of its unerased predecessor edges. A vertex is deleted with all incident edges, either when its counter is zero or when it enters a minimum augmenting path detected by FINDPATH. The counter of the free vertices is one at the start and during the phase, since they have no predecessor.

**Theorem 5.** *The running time for computing a maximum matching is  $O(n^2 \log^2 n)$  in the quantum adjacency matrix model and  $O(n\sqrt{m} \log^2 n)$  in the quantum adjacency list model.*

*Proof.* We show that a phase consisting of the four subroutines SEARCH, BLOSS-AUG, FINDPATH and TOPOLOGICAL ERASE can be implemented with quantum search in time  $O(n^{1.5} \log^2 n)$  in the adjacency matrix model and in time  $O(\sqrt{nm} \log^2 n)$  in the adjacency list model. Only  $O(\sqrt{n})$  such phases are needed for finding a maximum matching, see [HK73], [MV80]. We regard the above four subroutines:

**SEARCH:**

We perform a Breadth First Search to find the evenlevel and oddlevel of each vertex in  $G$  as follows: All free vertices of  $G$  get the evenlevel 0 and the other levels are infinite. SEARCH constructs simultaneously for every free vertex  $v$  of  $G$  a BFS tree to find the two level numbers of each vertex in  $G$ . In the adjacency model a vertex is found in  $O(\sqrt{n})$  quantum queries. Every vertex is processed at most twice, since we have two level numbers for each vertex. In the list model, processing a vertex  $v$  costs  $O(\sqrt{d_G(v) \cdot n_v})$  quantum queries, where  $n_v$  is the number of vertices adjacent to  $v$  with a infinite level number. Since  $\sum_v n_v \leq 2n$ , then the total quantum query complexity is upper-bounded by the Cauchy-Schwarz inequality:

$$\sum_v \sqrt{d_G(v)n_v} \leq \sqrt{\sum_v d_G(v)} \sqrt{\sum_v n_v} = O(\sqrt{mn}).$$

**BLOSS-AUG:**

The procedure BLOSS-AUG performs a Double Depth First Search, consisting in growing two DFS trees. With quantum search we perform these two DFS in  $O(n^{1.5})$  quantum queries to the adjacency matrix model and in  $O(\sqrt{nm})$  quantum queries to the adjacency list model, see Lemma 1.

**FINDPATH:**

The subroutine returns a path with a DFS starting at  $v_h$  to find  $v_l$ . Clearly with Lemma 1, the quantum query complexity is  $O(n^{1.5})$  in the adjacency matrix model and  $O(\sqrt{nm})$  in the adjacency list model.

**TOPOLOGICAL ERASE:**

We use Lemma 2, and the quantum query complexity of this procedure is the same as the above three subroutines.

In order to get the success probability of  $1 - 1/n$ , we need to amplify the success probability of each subroutine by repeating it  $O(\log n)$  times, see Remark 3. Considering this, we obtain the indicated quantum time complexity. ■

## 4 Weighted Matching

In this section, we look at weighted matchings in bipartite graphs. Let  $G = (V, E)$  be a graph,  $w(u, v)$  is the weight of an edge  $\{u, v\} \in E$ , if  $u$  is not adjacent to  $v$ , let  $w(u, v) = 0$ . We denote by  $N$  the largest edge weight and with  $W$  the total edge weight of  $G$ .

We regard the following two matching problems in weighted graphs:

**Maximum Weight Bipartite Matching:** Given a bipartite graph  $G$  with positive integer weights on the edges and without isolated vertices, compute a matching  $M$  in  $G$  such that the sum of the weights of the edges in  $M$  is maximum over all possible matchings.

**Minimum Weight Perfect Bipartite Matching:** Given a weighted bipartite graph  $G$ , compute a perfect matching  $M$  in  $G$  such that the sum of the weights of the edges in  $M$  is minimum over all possible perfect matchings.

#### 4.1 Maximum Weight Bipartite Matching

The best classical algorithms for computing a maximum weight matching in bipartite graphs with positive integer weights are developed by Gabow and Tarjan [GT89] with running time  $O(\sqrt{nm} \log(nN))$  and Kao, et al. [KLST01] with time complexity  $O(\sqrt{n}W/k(n, W/N))$ , where  $k(x, y) = \log x / \log(x^2/y)$ .

We give a quantum algorithm with running time  $O(n\sqrt{m}N \log^2 n)$  for computing a maximum weight matching in bipartite graphs. If the largest edge weight  $N$  is constant, then we get an  $O(n\sqrt{m} \log^2 n)$  time algorithm. For the construction of our quantum algorithm we use the decomposition theorem of [KLST01]. First we need some definitions and facts about a minimum weight cover in a bipartite graph.

**Definition 3** Let  $G = (X \cup Y, E)$  be a bipartite graph. A *cover* of  $G$  is a function  $C : X \cup Y \rightarrow \mathbb{N}$  such that  $C(x) + C(y) \geq w(x, y)$  for all  $x \in X$  and  $y \in Y$ . Let  $w(C) := \sum_{z \in X \cup Y} C(z)$  be the weight of  $C$ . The cover  $C$  is of *minimum weight*, if  $w(C)$  is the smallest possible value.

The algorithms for computing a maximum weight matching in bipartite graphs use the following problem:

**Minimum Weight Cover:** Given a bipartite graph  $G$  with positive integer weights, compute a minimum weight cover of  $G$ .

*Remark 4.* A minimum weight cover is dual to the maximum weight matching in a bipartite graph  $G$ , i.e. from a maximum matching in  $G$  we can find a minimum weight cover of  $G$  in time  $O(m)$ , see [BM76].

**Definition 4** Let  $G = (X \cup Y, E)$  be a bipartite graph and  $h \in \{1, \dots, N\}$  be an integer. Define  $G_h$  as the graph which is formed by the edges  $\{u, v\}$  of  $G$  with  $w(u, v) \in [N - h + 1, N]$  and the edge weight  $\{u, v\}$  of  $G_h$  is  $w(u, v) - (N - h)$ .

Let  $C_h$  be a minimum weight cover of  $G_h$  and  $G_h^*$  is formed by the edges  $\{u, v\}$  of  $G$  with  $w(u, v) - C_h(u) - C_h(v) > 0$  and the edge weight  $\{u, v\}$  of  $G_h^*$  is  $w(u, v) - C_h(u) - C_h(v)$ .

Now we present the Decomposition theorem of [KLST01].

**Theorem 6.** [KLST01] *Let  $h, G, G_h, C_h, G_h^*$  as in Definition 4 and let  $C_h^*$  be any minimum weight cover of  $G_h^*$ . If  $D : X \cup Y \rightarrow \mathbb{N}$  is a function such that for every  $u \in V(G)$ ,*

$$D(u) = C_h(u) + C_h^*(u),$$

*then  $D$  is a minimum weight cover of  $G$ .*

Using this theorem, a minimum weight cover of  $G$  can be computed with the following recursive procedure, see [KLST01].

---

**Algorithm 2** MINIMUM WEIGHT COVER

---

**Input:** Bipartite graph  $G = (X \cup Y, E)$  with positive integer weights.

**Output:** Minimum weight cover  $D : X \cup Y \rightarrow \mathbb{N}$ .

**Complexity:** **M:**  $O(n^2 N \log^2 n)$ , **L:**  $O(n\sqrt{m}N \log^2 n)$  quantum steps.

```

1: Construct  $G_1$  from  $G$ .
2: Find a minimum weight cover  $C_1$  of  $G_1$ .
3: Construct  $G_1^*$  from  $G$  and  $C_1$ .
4: if  $G_1^* = \emptyset$  then
5:   return $[C_1]$ 
6: else
7:    $C_1^* := \text{MINIMUM WEIGHT COVER}[G_1^*]$ 
8:    $D(u) := C_1(u) + C_1^*(u)$  for all  $u$  in  $G$ 
9:   return $[D]$ 
10: end if

```

---

The correctness of the algorithm follows from Theorem 6. We use our maximum matching quantum algorithm for computing a minimum weight cover of the graph  $G$ .

**Theorem 7.** *The quantum time complexity of the MINIMUM WEIGHT COVER algorithm is  $O(n\sqrt{m}N \log^2 n)$  in the adjacency list model and  $O(n^2 N \log^2 n)$  in the adjacency matrix model.*

*Proof.* We analyse the running time in the adjacency list model. We initialize a maximum heap in  $O(m)$  time to store the edges of  $G$  according to their weights.

Let  $T(n, W, N)$  be the running time of the MINIMUM WEIGHT COVER quantum algorithm. Let  $L$  be the set of all edges in  $G_1$ , i.e. the heaviest edges in  $G$ . Then Step 1 takes  $O(|L| \log m)$  time. In Step 2, we can compute a maximum matching of  $G_1$  in  $O(n\sqrt{|L|} \log^2 n)$  time steps, by using the maximum matching quantum algorithm. From this matching,  $C_1$  can be found in  $O(|L|)$  time, see [BM76]. Let  $L_1$  be the set of the edges of  $G$  adjacent to some vertex  $u$  with  $C_1(u) > 0$ . Step 3 updates every edge of  $L_1$  in  $O(l_1 \log m)$  time, where  $l_1 = |L_1|$ .

The total running time of steps 1 to 3 is  $O(n\sqrt{l_1} \log^2 n)$ , since  $L \subseteq L_1$ . The total weight of  $G_1^*$  is at most  $W - l_1$ . Step 7 uses then at most  $T(n, W - l_1, N')$  time, where  $N' < N$  is the maximum edge weight of  $G_1^*$  and it follows

$$T(n, W, N) = O(n\sqrt{l_1} \log^2 n) + T(n, W - l_1, N'),$$

where  $T(n, 0, N') = 0$ . We apply the procedure recursively for some positive integers  $l_1, l_2, \dots, l_p$  with  $p \leq N$  and  $\sum_{1 \leq i \leq p} l_i = W$ , it follows

$$T(n, W, N) = O\left(n \log^2 n \sum_{i=1}^p \sqrt{l_i}\right).$$

Since  $\sum_{i=1}^p \sqrt{l_i} \leq \sqrt{p \sum_{i=1}^p l_i}$ , then

$$T(n, W, N) = O\left(n \log^2 n \sqrt{p \sum_{i=1}^p l_i}\right) = O\left(n \log^2 n \sqrt{NW}\right).$$

Since  $W \leq Nm$  it follows  $T(n, W, N) = O(n\sqrt{m}N \log^2 n)$  in the list model. The running time for the matrix model follows setting  $m = n^2$ .

Now we use the algorithm by [KLST01] to recover a maximum weight matching of a bipartite graph  $G$  from a minimum weight cover of  $G$ .

---

**Algorithm 3** MAXIMUM WEIGHT MATCHING

---

**Input:** Bipartite graph  $G = (X \cup Y, E)$  with positive integer weights.

**Output:** Maximum weight matching  $M$ .

**Complexity:** **M:**  $O(n^2 N \log^2 n)$ , **L:**  $O(n\sqrt{m}N \log^2 n)$  quantum steps.

- 1:  $D := \text{MINIMUM WEIGHT COVER}[G]$
  - 2:  $A := \{\{u, v\} \in E \mid w(u, v) = D(u) + D(v)\}$
  - 3:  $H := (V, A)$
  - 4: Make two copies of  $H$ , call them  $H^a$  and  $H^b$ . For each vertex  $u$  of  $H$ , let  $u^a$  and  $u^b$  denote the corresponding vertex in  $H^a$  and  $H^b$ .
  - 5: Union  $H^a$  and  $H^b$  to form  $H^{ab}$ , and add to  $H^{ab}$  the set of edges  $\{(u^a, u^b) \mid u \in V(H), D(u) = 0\}$ .
  - 6: Find a maximum matching  $K$  of  $H^{ab}$ .
  - 7:  $M = \{(u, v) \mid (u^a, v^a) \in K\}$
- 

**Theorem 8.** *The running time of a quantum algorithm for computing a maximum weight matching in a bipartite graph is  $O(n\sqrt{m}N \log^2 n)$  in the adjacency list model and  $O(n^2 N \log^2 n)$  in the adjacency matrix model.*

*Proof.* We use the above algorithm. The graph  $H^{ab}$  has at most  $2n$  nodes and at most  $3m$  edges. The maximum matching  $K$  can be constructed by a quantum algorithm in time  $O(n\sqrt{m} \log^2 n)$  in the adjacency list model and in time  $O(n^2 \log^2 n)$  in the adjacency matrix model. ■

**Corollary 2.** *The running time of a quantum algorithm for computing a maximum weight matching in a bipartite graph with constant edge weight is  $O(n\sqrt{m} \log^2 n)$  in the adjacency list model and  $O(n^2 \log^2 n)$  in the adjacency matrix model.*

## 4.2 Minimum Weight Perfect Bipartite Matching

We give the quantum time complexity for computing a minimum weight perfect matching in a bipartite graph. For this task we use shortest paths.

**Shortest Paths:** Given a weighted graph  $G = (V, E)$  and a source vertex  $v_s$  of the graph, compute a tree  $T$ , such that the shortest paths from  $v$  to all the other vertices is in  $T$ .

The best classical algorithm for computing a minimum weight perfect matching in a bipartite graph computes shortest paths in a graph, see Cook [CCPS98]. The time complexity for such an algorithm is given by the following Theorem.

**Theorem 9.** [see CCPS98] *There is an algorithm for the minimum weight perfect matching problem for bipartite graphs with running time  $O(nS(n, m))$ , where  $S(n, m)$  is the time needed to solve the shortest path problem on a digraph with  $n$  vertices and  $m$  arcs.*

For the shortest path problem we use the quantum algorithm by Dürr, et al. [DHHM04].

**Theorem 10.** [DHHM04] *The shortest path problem can be solved by a quantum algorithm in time  $O(n^{1.5} \log^3 n)$  in the adjacency matrix model and in time  $O(\sqrt{nm} \log^3 n)$  in the adjacency list model.*

From this, we get the running time to compute the minimum weight perfect matching in a bipartite graph.

**Theorem 11.** *The running time of a quantum algorithm for the minimum weight perfect matching problem for bipartite graphs is  $O(n^{2.5} \log^3 n)$  in the adjacency matrix model and  $O(n\sqrt{nm} \log^3 n)$  in the adjacency list model.*

## Conclusion and Open Problems

We give a summary of the classical and quantum time upper bounds for the regarded matching problems in unweighted and weighted graphs:

Problem	Quantum Time Complexity	Ref.	Classical Time Complexity	Ref.
Maximal Matching	<b>M:</b> $O(n^{1.5} \log^2 n)$ <b>L:</b> $O(\sqrt{nm} \log^2 n)$	Theorem 1	$O(m)$	Trivial
Maximum Matching	<b>M:</b> $O(n^2 \log^2 n)$ <b>L:</b> $O(n\sqrt{m} \log^2 n)$	Theorem 5	$O(\sqrt{nm})$ $O(n^w)$	[MV80] [MS04]
Maximum Weight Bipartite Matching	<b>M:</b> $O(n^2 N \log^2 n)$ <b>L:</b> $O(n\sqrt{m} N \log^2 n)$	Theorem 8	$O(\sqrt{n} W)$ $O(\sqrt{nm} \log(nN))$	[KLST01] [GT89]
Minimum Weight Perf. Bip. Matching	<b>M:</b> $O(n^{2.5} \log^3 n)$ <b>L:</b> $O(n\sqrt{nm} \log^3 n)$	Theorem 11	$O(nS(n, m))$	[CCPS98]

We give some interesting open questions in the area of quantum matching algorithms:

1. Is the  $O(n^2 \log^2 n)$  quantum algorithm for computing a maximum matching optimal? The best quantum lower bound for this problem is  $\Omega(n^{1.5})$ . Is there a better upper bound for computing a maximum matching in bipartite graphs?
2. Gabow [Gab90] showed that both the minimum weight and the maximum weight matching problems can be solved in time  $O(n(m + n \log n))$ . He presents an algorithm in which a maximum weight augmenting path in a graph  $G$  can be found in time  $O(m + n \log n)$ . Enlarging in  $G$  the matching with the path, after  $n$  steps the maximum weight matching is found. It is open to find a quantum algorithm for the minimum weight and the maximum weight matching for general graphs improving the running time of the classical algorithm of Gabow.

## Acknowledgments

For helpful comments I am grateful to Jacobo Torán.

## References

- [Amb02] A. Ambainis, *Quantum Lower Bounds by Quantum Arguments*, Journal of Computer and System Sciences 64: pages 750-767, 2002.
- [AS06] A. Ambainis, R. Špalek, *Quantum Algorithms for Matching and Network Flows*, Proceedings of STACS'06, 2006.
- [BBHT98] M. Boyer, G. Brassard, P. Høyer, A. Tapp, *Tight bounds on quantum searching*, Fortschritte Der Physik 46(4-5): pages 493-505, 1998.
- [BCWZ99] H. Buhrman, R. Cleve, R. de Wolf, Ch. Zalka, *Bounds for Small-Error and Zero-Error Quantum Algorithms*, Proceedings of FOCS'99: pages 358-368, 1999.
- [BDFLS04] A. Berzina, A. Dubrovsky, R. Freivalds, L. Lace, O. Scegulnaja, *Quantum Query Complexity for Some Graph Problems*, Proceedings of SOFSEM'04: pages 140-150, 2004.
- [BM76] J. Bondy, U. Murty, *Graph Theory with Applications*, North-Holland, New York, 1976.
- [CCPS98] W.J. Cook, W.H. Cunningham, W.R. Pulleyblank, A. Schrijver, *Combinatorial Optimization*, John Wiley & SONS, INC, New York, 1998.
- [DHHM04] C. Dürr, M. Heiligman, P. Hoyer, M. Mhalla, *Quantum query complexity of some graph problems*, Proceedings of ICALP'04: pages 481-493, 2004.
- [Gab90] H. N. Gabow, *Data structures for weighted matching and nearest common ancestors with linking*, Proceedings of the 1st Annual ACM-SIAM Symposium on Discrete Algorithms: pages 434-443, 1990.
- [Gro96] L. Grover, *A fast mechanical algorithm for database search*, Proceedings of STOC'96: pages 212-219, 1996.
- [GT89] H.N. Gabow, R.E. Tarjan, *Faster scaling algorithms for network problems*, SIAM Journal on Computing 18: pages 1013-1036, 1989.

- [GY99] J. Gross, J. Yellen, *Graph Theory and its Applications*, CRC Press, London 1999.
- [HK73] J. E. Hopcroft, R. M. Karp, *An  $n^{5/2}$  algorithm for maximum matchings in bipartite graphs*, SIAM Journal on Computing 2(4): pages 225-231, 1973.
- [KLST01] M.-Y. Kao, T.-W. Lam, W.-K. Sung, H.-F. Ting, *A Decomposition Theorem for Maximum Weight Bipartite Matchings*, SIAM Journal on Computing 31: pages 18-26, 2001.
- [MS04] M. Mucha, P. Sankowski, *Maximum matchings via Gaussian elimination*, Proceedings of FOCS'04: pages 248-255, 2004.
- [MV80] S. Micali, V.V. Vazirani, *An  $O(\sqrt{nm})$  Algorithm for Finding Maximum Matching in General Graphs*, Proceedings of FOCS'80: pages 17-27, 1980.
- [NC03] M.A. Nielsen, I. L. Chuang, *Quantum Computation and Quantum Information*, Cambridge University Press, 2003.
- [Zha04] S. Zhang, *On the power of Ambainis's lower bounds*, Proceedings of ICALP'04, Lecture Notes in Computer Science 3142: pages 1238-1250, 2004.